



## Dual 5.25" Two-Way Floorstanding Loudspeaker

# RF-15

The RF-15 offers tremendous value and versatility in a high-performance floorstanding loudspeaker. Slender and compact, it still has the efficiency, power handling, and bass extension to deliver a potent sonic wallop. The RF-15 works equally well standing alone in a stereo music system or fronting a sophisticated home theater. And because it is perfectly matched cosmetically and sonically to the other Klipsch Reference Series loudspeakers, it allows terrific flexibility in system configuration.

The RF-15 uses a 1-inch titanium-dome compression driver tweeter for the high frequencies, loaded by a 5-inch square 90° x 60° Tractrix® Horn molded into the front of the enclosure. The horn raises the driver's efficiency and controls its radiation pattern to minimize detail-blurring reflections from walls, floor, and ceiling. Dual 5.25-inch Cerametallic™ cone woofers with rigid, low-resonance cast-polymer frames generate dynamic, room-filling bass. All drivers are magnetically shielded to prevent interference with direct-view television sets.

Amplifier connections are via two pairs of binding posts, which are strapped together for normal wiring. Removing the straps allows the speaker to be bi-wired. Magnetic posts hold the RF-15's low-diffraction grille securely in place, and the outrigger feet can be fitted with adjustable-height rubber pads or spikes. The rear-ported cabinet is available in a Black Ash or Light Cherry woodgrain vinyl finish.

- Very high sensitivity and power handling
- Tractrix Horn titanium dome compression driver tweeter for clean, detailed highs
- Cerametallic cone woofers with cast-polymer frames
- Bi-wire compatible inputs
- Magnetically shielded to prevent video interference

### SPECIFICATIONS

BANDWIDTH	46Hz-20kHz ± 3dB
SENSITIVITY	96dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2350Hz
POWER HANDLING	100 watts (400 watts peak)
ENCLOSURE TYPE	Bass-reflex via rear-firing port
DRIVE COMPONENTS	Two way system using one 1" (2.5cm) magnetically shielded, titanium dome compression driver with an integral 5" (12.7cm) square 90° x 60° Tractrix Horn and two 5.25" (13.3cm) magnetically shielded, Cerametallic cone woofers
WEIGHT	37 lbs. (16.8kg)
HEIGHT	36.9" (93.7cm) w/feet, 36" w/o feet
WIDTH	6.8" (17.3cm)
DEPTH	12.8" (32.5cm)
FINISH	Black Ash or Light Cherry woodgrain vinyl



www.klipsch.com  
1-800-KLIPSCH